

Title	階層型相互結合網のワームホール・ルーティングに関する研究
Author(s)	三浦, 康之
Citation	
Issue Date	2002-03
Type	Thesis or Dissertation
Text version	author
URL	http://hdl.handle.net/10119/921
Rights	
Description	Supervisor:堀口 進, 情報科学研究科, 博士

Wormhole Routing for Hierarchical Interconnection Networks

Yasuyuki Miura

School of Information Science,
Japan Advanced Institute of Science and Technology

January 10, 2002

Abstract

Three dimensional(3D) computers has been proposed. Hierarchical interconnection network TESH(Tori connected mESHes) and H3D torus(Hierarchical 3-D torus) has been proposed for interconnection network of large scale 3D multicomputer.

It have been showed that TESH and H3D torus are superior for network diameter and they are suitable for 3-D VLSI implementation by some works. However, dynamic network performance by sending packets in the network have not been evaluated. When many packets run in the wormhole routed interconnection network, deadlocks occur in the network. To avoid deadlocks, some virtual channels are added. Thus, to calculate the number of virtual channels and to propose routing algorithms are necessary. To propose adaptive routing algorithms and data mapping method are effective to improve network throughput. In this thesis, some fixed and adaptive routing algorithms are proposed and dynamic network performance are evaluated.

First, *in-a-line* allocation for link allocation method of TESH network and a routing algorithm for TESH are proposed , and the number of necessary virtual channels is calculated. As the result, it is shown that the number of necessary virtual channels is 2 or 4. Then the network performance of fixed routing for TESH network are evaluated by simulation. It is shown that 3 level TESH network show higher performance than other networks. Second, some adaptive routing algorithms are proposed to improve network performance. Then the network performance are evaluated. It is shown that adaptive routing algorithms for TESH network have higher performance than fixed routing. Third, new mapping policy of FFT for TESH network are proposed and the execution time are evaluated. By the simulation, it is shown that execution time of FFT in TESH is less than mesh. It is also shown that new mapping policy for TESH can reduce execution time. Finally, a routing algorithm for H3D torus network are proposed and the number of necessary virtual channels is calculated. As the result, it is shown that the number of necessary virtual channels is 2. The dynamic network performance of H3D torus which have 4096 PEs are evaluated by simulation. It is shown that the routing algorithm for H3D has a few lower latency and higher throughput than TESH.

Key Words: Hierarchical interconnection network, TESH, H3D torus, Wormhole routing